



ISI

ISIDest[®] Solvent recovery units

- Made in Germany -



ISIDest[®] LD 20 EX-E

Vessel capacity	15 – 20 litre
Power consumption	1,33 KW / 230 V / 1ph
Output / hour	approx. 5,0 litre
Working temperature	max. 200° C
Boiling range	50 – 160° C
Dimensions (L/W/H)	94 x 50,5 x 121 cm
Weight	70 kg
Marking	II 3G Ex IIB T2

Ideal system up to 300 litre a month.



ISIDest[®] LD 30 EX-E

Vessel capacity	25 - 30 litre
Power consumption	1,66 KW / 230 V / 1ph
Output / hour	approx. 7,0 litre
Working temperature	max. 200° C
Boiling range	50 – 160° C
Dimensions (L/W/H)	94 x 50,5 x 121 cm
Weight	85 kg
Marking	II 3G Ex IIB T2

Ideal system up to 500 litre a month.



ISIDest[®] LD 60 EX-E

Vessel capacity	50 - 60 litre
Power consumption	4,00 KW / 400 V / 3ph
Output / hour	approx. 18,0 litre
Working temperature	max. 200° C
Boiling range	50 – 160° C
Dimensions (L/W/H)	117 x 70 x 124 cm
Weight	120 kg
Marking	II 3G Ex IIB T2

Ideal system up to 1000 litre a month.



ISIDest[®] LD 120 EX-E

Vessel capacity	100 - 120 litre
Power consumption	6,00 KW / 400 V / 3ph
Output / hour	approx. 21,0 litre
Working temperature	max. 200° C
Boiling range	50 -160° C
Dimensions (L/W/H)	163 x 68 x 138 cm
Weight	180 kg
Marking	II 3G Ex IIB T2

Ideal system up to 2000 litre a month.

www.isi-umwelttechnik.de